

ECEF TECHNICAL SPECIFICATIONS

SCREWING TOOLS

FAMILY CLASSIFICATION	02610
DESCRIPTION	SDS-PLUS MAGNETIC BIT HOLDER FOR HAMMER DRILLS < 5KG
PRODUCT IMAGE	
LENGTH	80 mm
SHANK KIND OF STEEL	Cr40 - EN 10083-2
STEEL COMPOSITION % OF THE SHANK	C 0,38-0,45 - Si ≤ 0,40 - Mn 0,60-0,90 - P ≤ 0.035 - S ≤ 0,035 - Cr ≤ 0,90-1,10 Ni ≤ 0,30 - Mo ≤ 0,10 - Cu ≤ 0,030 C=Carbon - Si=Silicon - Mn=Manganese - P=Phosphorus - S=Sulfur - Cr=Chrome - Mo=Molybdenum Ni=Nickel - Cu=Copper - Ti=Titanium - Al=Aluminium
HARDENING TEMP.	1100°
HARDNESS	60 HRC
SHANK CONNECTON	SDS-PLUS ≈ Ø 10 mm  
MAGNET	4 DISCS OF NEODIMIDIUM ALLOY - TOTAL HEIGHT 4 mm
MAGNET COMPOSITION	BORON ALLOY - IRON - NEODYMIUM
SURFACE TREATMENT	Natural steel - Ground from the solid - smooth sandblasted finish - anti-corrosion treatment
REFERENCE TOOL	Manual drilling machines with SDS+ connection using the percussion function, high speed and good pressure. Hammer drills less than 5 KG 
PACKAGE	IN SINGLE PLASTIC WALLET

PERSONAL SECURITY WARNINGS



Always use safety glasses



In case of loud noise wear ear protection



Always wear protective gloves