

Rotary Hammer with SDS plus

GBH 240



Durable, reliable and superior – Drilling is now trouble-free with this tool

The most important data

Rated input power	790 W
Impact energy	2.7 J
Drilling dia. concrete, hammer drill bits	4 – 24 mm

Order number 0 611 272 100

Technical data

Performance data

Impact rate at rated speed	0 – 4,200 bpm
Rated speed	0 – 930 rpm
Additional data	
Rated input power	790 W
Impact energy	2.7 J
Tool holder	SDS plus
Voltage, electrical	230 V
Weight	2.8 kg
Drilling range	
Drilling dia. concrete, hammer drill bits	4 – 24 mm
Opt. appl. range concrete, hammer drill bits	6 – 14 mm
Drilling diameter in concrete with core cutters	16 – 68 mm

Noise/vibration information

Hammer drilling in concrete

Vibration emission value ah	19.3 m/s²
Uncertainty K	1.5 m/s²
Chiselling in concrete	
Vibration emission value ah	10.7 m/s²
Uncertainty K	1.5 m/s²

Product data sheet



Power tools for trade & industry

Advantages:

- Best in class drilling and chiseling through tough material made possible by gear housing set
- High drilling speed improves workload efficiency
- Aptly designed with interchangeable parts ensues easy maintenance
- Tailored to work long hours in hard working conditions

