7516 VDE Kraftform Safe-Torque Speed Torque screwdriver, 2.4-4.0 Nm, 9 x 2.4 Nm x 2.8 Nm x 3.2 Nm x 3.6 Nm x 4.0 Nm x 192 mm

7500 VDE Kraftform Safe-Torque Speed torque wrench series

EAN:	4013288233585	**Size:**	199x66x36 mm
Part number:	05075876001	**Weight:**	119 g
Article number:	7516 VDE	**Country of origin:**	CZ
		Customs tariff number:	82054000

- VDE bladeholding torque screwdriver 7516 with 5 pre-set values (2.4; 2.8; 3.2; 3.6; 4.0 Nm)
- Speed: Extremely fast setting of desired torque values
- Safe: Slip-over torque function which can not be overtightened - for clockwise/counterclockwise torque operation
- Torque Lock function: for high tightening and loosening moments without torque
- With fast-rotating sleeve and mounting for Wera VDE interchangeable blades

VDE-insulated torque wrench handle with 9 mm hexagon mounting; solely for Wera Kraftform Kompakt VDE blades. For professional screwdriving/fine adjustment AND for torque operated screwdriving. Slip-over torque function which can not be overtightened - for clockwise/counterclockwise torque operation. With five selectable tightening torques clockwise/counterclockwise (2.4; 2.8; 3.2; 3.6; 4.0 Nm), which can be set very quickly. One fixed position (Torque Lock) for unlimited loosening and tightening moments. With fast-rotating sleeve for easy wielding of the tool whilst screwdriving.

Web link
https://products.wera.de/en/new_products_2025_7500_vde_kraftform_safe-torque_speed_torque_wrench_series_7516_vde.html

Wera Werkzeuge GmbH
Korzerter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de

7516 VDE Kraftform Safe-Torque Speed Torque screwdriver, 2.4-4.0 Nm, 9 x 2.4 Nm x 2.8 Nm x 3.2 Nm x 3.6 Nm x 4.0 Nm x 192 mm

7500 VDE Kraftform Safe-Torque Speed torque wrench series

VDE bladeholding torque screwdriver 7516 with 5 pre-set values (2.4; 2.8; 3.2; 3.6; 4.0 Nm)

Individually tested

The individual testing at 10,000 volts, in accordance with IEC 60900, ensures safe working with loads up to 1,000 volts.

Handle for Wera VDE blades

The Safe-Torque Speed VDE bladeholding screwdriver is suitable solely for Wera VDE blades.

Five selectable tightening torques

Five selectable tightening torques (2.4; 2.8; 3.2; 3.6; 4.0 Nm) and one fixed position (Torque Lock) for unlimited tightening and loosening moments.

Quick torque setting

Quick setting of the selectable tightening torque values.

Excess-load signal

Distinctly audible and noticeable excess-load signal when the pre-set torque is reached.

Safe torque transfer



The slip-over torque mechanism for clockwise/counterclockwise torque operation prevents unintentional application of excessive torque.

Further versions in this product family:

	mm	Nm	Nm	Nm	Nm	Nm	mm
05075876001	9	2.4	2.8	3.2	3.6	4.0	192

Web link
https://products.wera.de/en/new_products_2025_7500_vde_kraftform_safe-torque_speed_torque_wrench_series_7516_vde.html

Wera - 7516 VDE
05075876001 - 4013288233585

Wera Werkzeuge GmbH
Korzerter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de