

ECEF TECHNICAL SPECIFICATIONS

SCREWING TOOLS

FAMILY CLASSIFICATION	04860
DESCRIPTION	PHILLIPS TYPE SCREW BIT DIN 5260 PH HRC60 - HEXAGONAL DRIVE DIN 3126 1/4" (6,35)
PRODUCT IMAGE	
SHAPE	PH 1-2 
LENGTH	200 mm
KIND OF STEEL	S2 - UNS T41902 - 73 MOV
COMPOSITION%	C 0,40-0,55- Si 0,90-1,05 - Mn 0,30-0,50 - P ≤ 0.030 - S ≤ 0,03 - Mo 0,30-0,60 V ≤ 0,50 - Ni+Cu ≤ 0,75 C=Carbon - Si=Silicon - Mn=Manganese - P=Phosphorus - S=Sulfur - Cr=Chrome - Mo=Molybdenum V=Vanadium - Ni=Nickel - Cu=Copper
HARDENING TEMP.	1100°
HARDNESS	60 HRC
CENTRAL TORSION AREA	50 HRC it absorbs the torsion force, the vibrations and torque picks
SHANK	HEXAGONAL 1/4" DIN3126(6,35mm)
MANUFACTURING PROCESS	FULLY GROUND FROM THE SOLID, with CAO System, that grants quality control and product homogeneity.
SURFACE TREATMENT	Natural steel - ground - smooth bright finish - anti-corrosion treatment
USING ON	Impact screwdriver power drills / manual use
PACKAGE	IN PLASTIC WALLET WITH 1 SINGLE Pc.

PERSONAL SECURITY WARNINGS



Always use safety glasses



In case of loud noise wear ear protection



Always wear protective gloves